

AI Workplace Occupancy Sensor

VS121



VS121

VS121-P

Milesight VS121, is an AI workplace sensor designed to monitor occupancy and utilization in modern workspace, which can reach up to 98% recognition rate based on its AI algorithm. Milesight VS121 has dual versions transmitting data through LoRaWAN® or Ethernet for different applications.

Based on standard LoRaWAN® protocol, VS121 can work with Milesight LoRaWAN® gateway and mainstream LoRaWAN® network servers. They are equipped with Wi-Fi for easy configuration without any configuration tools.

With Ethernet transmission, VS121-P is available to provide more applications. Rich serial interfaces such as DI, DO, and RS485 are provided in VS121-P for various scenarios. VS121-P supports data push via HTTP/MQTT for easily integration and allows for remote management via Milesight DeviceHub or Milesight Development Platform.

◆ Features

Shared Values

- Recognition rate is up to 98% based on advanced AI identification and analysis technologies
- Wide installation height and detection range with two versions for various scenarios
- Support regional people counting, occupancy detection and dwell time detection

- Support up to 16 mapped regions for detection
- Allow for bi-directional line-crossing people counting and people flow analysis
- Smart U-turn counting to filter redundant counting of people wandering around the area
- Support people flow analysis to calculate the traffic from different directions
- Support normal or blur mode and privacy masks up to 8 regions
- Support data retransmission to collect data securely

LoRaWAN® Version Only

- Compliant with GDPR without images collected, free from privacy concerns
- Equipped with Wi-Fi for web GUI configuration
- Support Milesight D2D protocol to enable ultra-low latency and directly control without gateway
- Function well with standard LoRaWAN® gateways and network servers

PoE Version Only

- Support scheduled detection
- Support Milesight DeviceHub or Milesight Development Platform management remotely
- Adapt to more applications with rich industrial interfaces
- DC or PoE power supply optional
- High compatibility of data transmission via Ethernet port (HTTP/MQTT/HTTP API)

◆ Specifications

Model	VS121	VS121-P
People Counting		
Field of View	Standard Version: 190 ° Horizontal, 112 ° Vertical High Ceiling Mount Version: 129.4 ° Horizontal, 68.4 ° Vertical	
Full Monitored Area	Standard Version: 78m ² (R = 5m, H = 3m) High Ceiling Mount Version: 126m ² (L=18m, W=7m, H= 7m)	
Installation Height	Standard Version: 2.5m to 4m High Ceiling Mount Version: 5m to 7m	
Detection Rate ¹	Region Counting: Up to 95% Line Crossing Counting: Up to 98% People Flow Analysis: Up to 98%	
Advanced Function		
Regional People Counting & Dwell Time	Up to 16 areas (up to 10 sides for each area) for regional people counting and dwell time detection	

Detection		
Bi-Directional People Counting		Support
U-turns Filtering		Filter redundant counting of people wandering in the bi-directional people counting areas
People Flow Analysis		Calculate the traffic of different directions at most 4 edges
Privacy Mask		Up to 8 privacy masks to cover certain areas
Data Retransmission		Support 3000 data retransmission packets
LoRaWAN® Transmission		
Protocol	LoRaWAN®, Milesight D2D	
Frequency	CN470/IN865/RU864/EU868/US915/AU915/KR920/AS923-1&2&3&4	
Tx Power	16 dBm (868 MHz)/20 dBm (915 MHz)/19 dBm (470 MHz)	---
Sensitivity	-137 dBm @300bps	
Mode	OTAA/ABP Class C	
Ethernet Transmission		
Ethernet Port		1 × RJ45 10/100 Mbps (PoE PD)
Network Protocol	-	MQTT(s), HTTP(s), RTSP, NTP, SSH,etc.
Other Interfaces		
Wi-Fi	IEEE 802.11 b/g/n, 2.4GHz (AP Mode for Configuration)	-
DI/DO	-	1/1
Serial Interface	-	1 × RS485 (Under development)
Button	1 × Reset Button, 1 × Wi-Fi Button	1 × Reset Button
LED Indicators	1 × Wi-Fi	1 × Status
Power Input	-	2-pin 3.5 mm Terminal Block
Physical Characteristics		
Power Supply	DC 5V/ 1.5A by Type-C Port	1. DC 5V/2A by Terminal Block 2. 802.3af PoE
Power Consumption	3.5W	1. DC:3.5W 2. POE:4.5W
Operating Temperature		-5°C ~ +55°C
Storage Temperature		-20°C ~ +60°C

Relative Humidity	0 ~ 95% (Non-condensing)	
Color&Weight	White/Black (Optional), 126.9g	White, 186g
Dimension	85 × 85 × 20 mm (3.35 × 3.35 × 0.79 in)	85 × 85 × 30 mm (3.35 × 3.35 × 1.18 in)
Installation	Ceiling Mounting	
Approvals		
Regulatory	CE, FCC, RoHS	

◆ Installation Height

To better utilize the advantage of AI algorithm, it's recommended to follow the below installation heights:

Object	Height	Note
Sitting object	>2.5 m (8.2ft)	Commonly used for region people counting
Standing object	> 3 m (9.8ft) (the optimum height is 3m)	Commonly used for line cross counting

It's recommended to refer to below detection ranges² for people counting at different heights for accurate recognition:

Installation Height (m)	Detection Range (m ²)
2.5	3.0 × 4.0
3.0	4.4 × 5.7
3.5	4.9 × 6.4
4.0	5.6 × 7.4

For high ceiling mount version, the detection ranges are as below:

Installation Height (m)	Detection Range (m ²)
5.0	3.5 × 10.0
6.0	4.5 × 12.0
7.0	5.5 × 14.0

¹ Tested under the recommended detection range.

² The actual detection range may vary based on the height of the target individual.

